



## EPS - Datasheet

### Series EPS/HPE

The microprocessors controlled Power Supplies »EPS/HPE« of EPS Electronic Power Supplies are due to their compact construction in a 19" enclosure are ideally suited to easily transition into cost effective production and bulk power solutions, i.e. semiconductor tests and burn-in.

Available are units with high output power with 20, 30, 40, 45, 60, 80, 100, 120 as well 150kW and output voltages between 0-1500V DC. The Power Supplies can operate in Constant Current and Voltage mode. The devices also come with the possibility of parallel connection for standard.

Actual values and set values are clearly represented on the graphic display.

For remote control using a PC or PLC the devices are provided as standard with an RS232 interface as well as an isolated analog interface on the rear side.

Optionally are available a RS485, USB, GPIB or an Ethernet interface.

Further options are the »EPS/ATE« without front operation and a DC input from 250-750V. Also, other AC input voltages are available on request.

Energy efficiency: high efficiency, Stand-by switch, temperature controlled fans

Scope of delivery:  
Power Supply Unit  
Operation Manual

## EPS/HPE-100800125 Laboratory Power Supply

---



EPS/HPE 30kW front

### General datas

Technology	Switching
Operation modes	CV. CC
Mains	400 VAC, 3ph +-10%
Input frequency	47-63Hz
Power factor	>0,98
Display	LCD
Voltage resolution	3 digits
Voltage accuracy	2V
Voltage Stability Load	+ - 0,05% F.S +2mV
Voltage Stability Mains	+ - 0,02% F.S
Response time	<3ms (10-90%)
Rise time Voltage	40ms(0-100%)
Current Resolution	3 digits
Current Accuracy	0,026A
Current Stability Load	+ - 0,05% F.S +20mA
Current Stability Mains	+ - 0,02% F.S
Output Current Limitation	Standard
Overvoltage category	2
Overheat protection	Standard
Isolation In-/Output	3000V DC
Isolation Output/Enclosure	2000VDC
Protection class	1
Parallel operation	Standard
Current sharing	Standard
Cooling	Fan

Series EPS/HPE

Operation temperature	0-50°C
Storage temperature	-20...70°C
Humidity	<80% n.c
Attitude	<2000m
Design	19 inch
Standards	EN 60950, EN 61000-6-4/2, EN61010-1
Power fail	Standard
Output Preset	Standard

**Interfaces**

Analog Isolation	Standard
Accuracy Interface	0,05%+2mV
USB Interface	Option EPS/HPE-USB
RS232 Interface	Standard
RS485 Interface	Option EPS/HPE-RS485
GBIP Interface	Option EPS/HPE-IEEE
Ethernet Interface	Option EPS/HPE-LAN

**Technical datas**

Output Voltage	0-900 VDC
Output Current	0-125 A
Output Power	100000 W
Input Current	229A
Efficiency	<92%
Ripple U	400
Ripple I	<0,5%(pp), <0,4%(rms)
Dimensions in mm (WxHxD)	19" x 1111 x 800
Weight	265 kg
Order code	113606

**Options**

Option 1	Without frontpanel EPS/HPE-ATE
Option 2	DC input 250-750V EPS/HPE-DC



EPS/HPE 30kW rear



EPS/HPE 60kW rear

---

Subject to modification without notice, errors and omissions excepted

EPS Stromversorgung GmbH  
Electronic Power Supplies  
Alter Postweg 101 86159 Augsburg  
Tel.: +49 (0) 821 570451-0  
Fax.: +49 (0) 821 570451-25  
E-mail: [info@eps-germany.de](mailto:info@eps-germany.de)  
[www.eps-germany.de](http://www.eps-germany.de)