



## EPS - Datasheet

### Series EPS/3000/4000 B

EPS's universal power supplies »EPS/3000/4000 B« offer versatile functionality, a practical housing design and excellent values.

There are no ventilation slots in either the top or base of the units, also no external heat sinks. This attention to safety and protection makes it ideal for schools and universities as well as test and development laboratories and industry.

The adjustable 0-30V and 0-300V AC voltages of the AC output are also available as DC output, via a rectifier and switchable capacitor filter.

The model »EPS/3048B has an adjustable output from 0-30V AC and DC at 5A.

At the model »EPS/3050B« the outputs 0-30V AC and DC or 0-300V AC and DC can be used only alternatingly, because of an internal range switching.

The model »EPS/3051B« is stabilized power supply with Power-MOSFET end stages. The output voltage and output current are adjustable from 0-32V and 0-5A.

The »EPS/4000B« is with a variable transformer for a continuously variable output voltage of 0-260V AC at 3A or 4,5A. A further transformer provides a fixed output voltage of 230V AC at 2A. The AC outputs are available on safety sockets on the front panel. Output 3 is a regulated stabilized DC voltage of 3-6V/2A.

Output 4 is a stabilized power supply with Power-MOSFET end stages. Output voltage and output current are adjustable from 0-32V and 0-5A, too. Output 5 has several AC voltages with 2A maximum load.

All models feature for output voltage and output current illuminated 3-digit volt and ampere meters. Galvanic isolation between all outputs and mains power is provided.

Scope of delivery:

Power Supply

Mains cable (CEE)

Operation manual

## EPS/4000 B-4,5 Universal Power Supply

---



EPS/4000B Front

### General data

Technology	Linear
Operation modes	CV
Mains	230 VAC $\pm 10\%$
Input frequency	50/60Hz
Display	Digital 3.0
Overheat protection	Standard
Cooling	Fan
Operation temperature	0-40°C
Storage temperature	-25-70°C
Humidity	0-95% n.c
Design	Desktop
Standards	EN 61010-1, EN 61326

### Interfaces

### Technical data

Output Voltage	230 VAC
Output Voltage 2	0-260 VDC
Output Voltage 3	3-6 VDC
Output Voltage 4	0-32 VDC
Output Voltage 5	3V/12V/18V/24V AC
Output Current	2A
Output Current 2	4,5A

### Technical data

Output Current 3	2A, stabil.
Output Current 4	0-5A, stabil.
Dimensions in mm (WxHxD)	480 x 180 x 270
Weight	40kg
Order code	200383



EPS/3000B-Rear

Subject to modification without notice, errors and omissions excepted

EPS Stromversorgung GmbH  
Electronic Power Supplies  
Alter Postweg 101, 86159 Augsburg/Germany  
Tel.: +49 (0) 821 570451-0  
E-mail: sales@eps-germany.de  
www.eps-germany.de