

EPS - Datasheet

Series EPS/HC 4000-WC

The series »EPS/HC 4000-WC« from EPS Electronic Power Supplies is a range of adjustable, switched mode high current sources offering standard output voltages from 6V up to 30V, output currents up to 2000A and output power ratings up to 40 kW (different other output voltages/currents/power ratings upon request). The units are used in high-power environments such as electroplating and Plasma (surface treatment, hardening), multiple industrial applications (powering of electric engine starters, DC motors, automatic end-of-line test systems for the testing of contactors, relays, switches, Steel wire ropes/rails as well as cables) and heavy duty components in general. All units are short-circuit proofed and overload protected. A switch-off, with a defined restart, takes place at mains undervoltage or overvoltage.

The heavy duty switch mode power stage is build in a 19" housing in 2 different form factors.

The modules are by standard without control.

The high-current power supplies can be controlled optionally via the built-in isolated analog interface. As an option the operation and control are very simple with the backlight 3-line LCD display »EPS/HC280« and a tough touch panel. Optionally digital interfaces (modules) for RS485, ProfiBus/Net, USB (on analog), TCP/IP and EtherCat are available to control all the functions via a PC. The DC sources with high output current are available with Cu bars and with high output voltage with HDFK terminals.

Remote sensing can be optionally done via a dedicated input which is directly connected to the test equipment, in order to compensate the voltage drops on the lines.

There is also a special version with an output voltage of 1000V and with a output power of 20 and/or 40 kW available.

With the reverse polarity option, the power supply can also be used as a bipolar device (output voltage up to 60V max).

Energy efficiency: High efficiency, water cooling

Scope of delivery:

Power Supply

Waterconnection via 1/2 inch

or bayonet

Operation Manual

EPS/HC 40006-2000-WC DC Current Source



EPS/HC 4000 Water Cooling

General data

Technology	Switching
Operation modes	CV. CC
Mains	3x400 VAC +/- 10%
Input frequency	50/60Hz
Power factor	>0.95
Input Current Limitation	Standard
Display	Option EPS/HC280
Voltage resolution	Opt. 0,01V
Voltage accuracy	<0,5%
Current Resolution	Opt. 0,1A
Current Accuracy	<1%
Output Current Limitation	Standard
Overheat protection	Standard
Protection class	IP53
Series operation	Standard
Parallel operation	Standard
Cooling	Water cooling
Operation temperature	5-40°C
Humidity	85% n.c
Attitude	1000m NN
Design	19 inch
Standards	EN55011(A,B) EN61000-6-4 EN61000-6-2 EN50178
Power fail	Standard
Alarmmanagement	Optional

Interfaces

Analog Isolation	Opt. EPS/HC IF-DASI
USB Interface	Option EPS/IF-UTA(101994)
RS485 Interface	Option EPS/HC IF-RS485
Profibus	Option EPS/HC IF-PB1
Ethernet Interface	Option EPS/HC IF-LAN

Technical data

Output Voltage	0-6 VDC
Output Current	0-2000 A
Output Power	12000 W
Input Current	21A
Efficiency	~95%
Ripple U	<1%
Remote Sensing	Option EPS/HC Sense
Dimensions in mm (WxHxD)	482 x 266 x 515
Weight	~120 kg
Order code	202301



EPS/HC280 Control Panel



Subject to modification without notice, errors and omissions excepted

EPS Stromversorgung GmbH
Electronic Power Supplies
Alter Postweg 101, 86159 Augsburg/Germany
Tel.: +49 (0) 821 570451-0
E-mail: sales@eps-germany.de
www.eps-germany.de