



EPS - Datasheet

Series EPS/FTP/T

EPS's microprocessor controlled AC/AC Frequency Converters »EPS/FTP/T« series provide a 3-phase sine wave output from a 1- or 3 phase input. There are output power of 750 VA to 9000 VA available. The 50, 60 or 400 Hz output frequency and output voltage 200/115V and 400/230V AC are factory-set. The floating outputs are isolated from each other and can be operated as "Y" configuration or three individual outputs. In "Y" configuration, the centre (neutral) have to be grounded. The units can be shut-down electronically by a control switch on the front-panel of the unit. A remote shut-down option is also available.

Other options are Power Fail Alarm, ruggedizing against shock and vibrations, extended temperature range (-40°C until +70°C) and a 19" cabinet.

The series is characterized with full electronic protection and low input and output noise. For example, the converter has an output overload protection (OLP) and a current limiting with short circuit protection. Including is conformal coating of the units, too.

Common application fields for the 19 "-devices and/or chassis mounting, are simulations of the electrical system to the testing according to customer conditions, power adjustments to the supply of industrial plants as well as 400Hz fixed frequency converters for the avionics stationary as well as mobile. As standard, the converters are supplied with screw terminal block input/output.

The devices are CE, UL as well as CSA certified.

Energy efficiency: high efficiency, high MTBF

Scope of delivery:
AC/AC Converter
Operation manual on request

EPS/FTP6000-EA-19 AC/AC Frequency Converter



EPS/FTP6K 19rack

General data

Technology	Switching
Operation modes	CV
Mains	195-264 VAC 1-ph
Input frequency	47-63Hz
Input Current Limitation	Standard
Voltage Stability Load	+-6% (10-100%)
Overheat protection	Standard
Isolation In-/Output	2250V DC
Cooling	Fan
Operation temperature	0-50°C
Humidity	5-95% n.c.
Design	19 inch
Standards	EN62368-1, EN55022 C.A, EN61000-3-2, UL458
ruggedized	Option EPS/F..RG

Interfaces

Technical data

Output Voltage	208/120 VAC 3ph+N
Output Current	9,6A /ph.
Output Power	6000 VA
Input Current	54A
Distortion	<5% (100%)

Series EPS/FTP/T

Technical data

Output Frequency	60Hz
Efficiency	80% typ-
Ripple U	<500mVrms (BWL20MHz)
Dimensions in mm (WxHxD)	19" x 267 x 457
Weight	28 kg
Order code	400231

Option 2	Expanded temperature range EPS/F..CT
Option 3	Floating Output EPS/F..FO
Option 4	Remote Shut Down EPS/F..RS
Option 5	Chassis mounting
Option 6	Output fail alarm EPS/F..OF



EPS/FTP/T 6000-19rack mount



EPS/FTP/T 1500/3000 Chassis